

CLASSIC

Resilience^{SR}
ENDURING PROTECTION

THE
SYMPHONY
COLLECTION™

							
White SCL-042	Marshmallow SCL-108	Creamery SCL-104	Doe SCL-016				
							
Kilimanjaro SCL-024	Chamois SCL-102	Buff SCL-009	British Tan SCL-008				
							
Papyrus SCL-029	Stone SCL-040	Granite SCL-019	Taupe SCL-041				
							
Fog SCL-106	Water SCL-115	Reef SCL-111	Bayou SCL-101			Lake SCL-107	Blue Ridge SCL-006
							
Scallion SCL-113	Celery SCL-013	Sage SCL-036	Oregano SCL-110			Orchard SCL-028	Spruce SCL-039
							
Chamomile SCL-103	Cashew SCL-011	Saffron SCL-035	Mustang SCL-109	Persimmon SCL-030	Cayenne SCL-012		
							
American Beauty SCL-003	Tandoor SCL-114	Rouge SCL-032	Brick SCL-007	Claret SCL-015	Grape SCL-020		
							
Saddle SCL-034	Mocha SCL-026	Hazelnut SCL-021	Burgundy SCL-010	Fudge SCL-018	Chocolate SCL-014		
							
Currant SCL-105	Iris SCL-022	Admiral SCL-001	Pewter SCL-031	Navy SCL-027	Black SCL-005		

CLASSIC

APPLICATIONS Hospitality, Healthcare, Contract, Education, Marine, Automotive & RV, Residential

GENERAL SPECIFICATIONS

Width 54"
Roll Size 40 Yards
Weight 29 Ounces per Linear Yard
Backing 100% Brushed Polyester Knit

PERFORMANCE SPECIFICATIONS

Abrasion Resistance 500,000+ Double Rubs ASTM D 4157-10
Wyzenbeek / CFFA-1A
Mildew Resistance Pass ATM G21-96 / CFFA-120
Anti-Bacterial Pass AATCC 147 / CFFA-300
Anti-Microbial Pass ASTM G21-96 / CFFA-120
Ultra Violet Resistance 1000 Hours per ASTM 154-06/CFFA-2
Cold Crack -20° F Federal Standard No. 191A-Method 5874 / CFFA-6
Sulfide Stain Resistant

Stain Resistance per CFFA 141

Ketchup	5
Mayonnaise	5
Soy Sauce	5
Butter	5
Tea	5
Whiskey	5
Coffee	5
Soda	5
Blood	5
Urine	5
Iodine/Betandine	5
Mascara	5
Suntan Lotion	5
Hairspray	5
Lipstick	5
Liquid Foundation	4.5
Motor Oil	5


Grading: Class 5-Excellent;
Class 4-Good; Class 3-Fair;
Class 2-Poor; Class 1-Very Poor

FLAMMABILITY REQUIREMENTS *

California Fire Code Technical Bulletin No. 117, Section E
BIFMA
UFAC Class 1
MVSS 302
NFPA 260
Boston Fire Department Code Test BFD IX-1
Port Authority of New York / New Jersey
IMO A.652 (16) 8.2 and 8.3
ASTM E84: Class 1 or A Rating (Adhered & Un-Adhered)

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Classic will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.



Resilience^{SR} represents the latest technology in Faux Leather and Vinyl Protection, enhancing performance where it is needed the most:

STAIN RESISTANCE: With proper care, materials treated with **Resilience^{SR}** can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

ANTI-MICROBIAL & ANTI-BACTERIAL PROTECTION: Products treated with **Resilience^{SR}** are engineered to inhibit bacterial growth, as well as fungus, mold and mildew spores, resulting in a more hygienic environment.

ABRASION RESISTANCE: **Resilience^{SR}** provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material.

Resilience^{SR} is not visible, and does not affect the hand of the material. **Resilience^{SR}** is engineered to last, even after repeated cleaning and wear. Specify **Resilience^{SR}** for the most demanding healthcare and hospitality applications.

**GRADE D
2016**

RFM[®]  **seating**

619 S.W. Wood St., Hillsboro, OR 97123 T:800.447.5542 F:800.734.6377 www.rfmseating.com

PROP 65 WARNING: This product may contain a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

* This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. 11.15